

PHILIPS

Lighting



Blue (/52) TL/TL-D

TL 20W/52 SLV/25

By emitting light almost entirely within the 400 to 500 nm bandwidth and peaking at 450 nm, Philips TL/TL-D color 52 lamps have no radiation from the short wave UVB. waveband. They are therefore suitable to be used in systems for applications such as Agriculture and Neonatal Jaundice Phototherapy

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take them to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Life to 50% Failures (Nom)	9,000 hour(s)
Useful Life (Nom)	2,000 hour(s)
Light Technical	
Color Code	52
Luminous Flux	318 lm
Chromaticity Coordinate X (Nom)	154
Chromaticity Coordinate Y (Nom)	69
Operating and Electrical	
Power Consumption	19.3 W
Lamp Current (Nom)	0.36 A
Voltage (Nom)	59 V

Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Shape	T38
Net Weight (Piece)	156.000 g
Approval and Application	
Mercury (Hg) Content (Nom)	8.0 mg
CE mark	Yes
Product Data	
Order product name	TL 20W/52 SLV/25
Full product name	TL 20W/52 SLV/25
Full product code	871150064302540
Order code	928003505203
Material Nr. (12NC)	928003505203
Numerator - Quantity Per Pack	1

Blue (/52) TL/TL-D


EAN/UPC - Product/Case	8711500643025
Numerator - Packs per outer box	25
EAN/UPC - Case	8711500643032

Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL 20W/52 SLV/25	40.5 mm	589.8 mm	596.9 mm	594.5 mm	604 mm

Photometric data



Spectral Power Distribution Colour - TL 20W/52 SLV/25

