



Features

- **Automatic gain control (AGC)** Maintains optimal brightness of the image even in lower light situations
- **Iris mode selection** Permits selection of either AVERAGE or PEAK exposure measurement. Normally, the AVERAGE setting is used. However, in certain situations, such as observation of the gastric angle, the PEAK setting may be selected. This setting reduces the light on the brightest part of the image, thus allowing more accurate observation and diagnosis.
- **Fast Shutter** For most observations, shutter speed of 1/60 second is used. However, to eliminate blurred photographs when the subject or videoscope is moving, you may select a higher shutter speed of 1/250 second
- **Hue Adjustment Level Indicator**
This control for red and blue provides a broad range of adjustment for fine-tuning the image to meet your individual preference.

The Olympus CV-100 Video Processor provides high resolution, true color video imaging without image “break-up” due to developments in instantaneous single plate color chip technology.



Typical Manufacturer's Image

Olympus 100 Video Processor

Specifications

Mode	Either FIELD or FRAME may be selected. Normally, the FIELD mode is used to obtain movement-free frozen images. However, the FRAME mode enhances vertical resolution, and may be preferred for diagnostic observation of small areas.
Enhancement Selector	Provides three levels of outline or edge enhancement, which can be useful for achieving clearer images of protruding portions of the image and for detailed observation
Sub Screen	When set to ON, a subsidiary image appears at the bottom left of the monitor when the FREEZE button is activated on the videoscope. This feature allows you to maintain a live image at all times while simultaneously observing the frozen image in detail.
VTR Switch (Start/Stop)	For recording the monitor image on videotape. (The VTR must be in record "pause" mode)
Videoprinter Release Switch	For printing the monitor image
Monitor Output Selector	Allows selection of video signal (RGB, Y/C, NTSC) for out to various types of monitor and video ancillary devices. The Y/C output provides optimum utilization of S-VHS videotape recorders.
Remote Switch Function Display	The videoscope has four remote switches and the lighted display indicates which functions have been pre-selected.
Record Destination Selector	A maximum of four still-image recording systems (video image recorder, magnetic disk, videodisk, and digital filter) can be connected and controlled from this selector. This does not control the Videoprinter function.
Videoscope Cable Holder	Securely cradles the videoscope cable connector when not connected to the videoscope to prevent accidental damage.



Soma Technology Inc.
166 Highland Park Drive
Bloomfield, CT 06002 • USA
1.800.438.7662
www.SomaTechnology.com

Note: The technical data given in this publication is for general information and are subject to change without notice. Actual configuration on the unit may vary. Contact our sales representatives for a complete list of details.