




GIMA

GIMA D-600 DIGITAL SEALING MACHINE with validation system

Code: 35915
Category: Thermosealing Machines
Unit of sale: 1 pc.
Minimum order: 1
Type: No medical device



EAN13: 8023279359152

Description: With validation system complying with ISO 11607 P.2 rule. GIMA 600 has been designed to continuously monitor, during the whole sealing phase, all critical process parameters: Temperature, Speed, Pressure. It guarantees sealing in full respect of EN 868-5 / ISO 11607 P.2 rules, provides real-time monitoring of working temperature, applied force and running speed, time used during the sealing process. All sealing data can be recorded on an external carrier which can be linked to the sealer through a USB port placed on the unit. D 600 is controlled by a microprocessor. Operator's interface is a clear 2 line display, integrated in an ergonomic keyboard placed at the upper side of the sealer in an extremely user friendly position. Simple use, high reliability, D 600 is the ideal solution for hospitals and clinics aiming to use units which fully comply with the new ISO standards. Made in Italy.

Technical Specifications:

- Sealing width: 12 mm
- Multiline sealing
- Sealing speed: 6 m/min
- Temperature adjustment: 10-200°C ± 5 °C
- Alarms functioning out of tolerance
- Automatic stand-by
- 4 key membrane keyboards
- LCD 2 lines 6 characters
- Multilanguage menu
- USB port
- Data storage on pendrive
- Power: 230V / Hz 50 – single-phase (on request 60Hz)
- Max electrical input: 500W
- Dimensions: 473 x 235 x 181 mm
- Weight: 12,5 kg