



Transducers

ACUSON P500 ultrasound system

siemens-healthineers.com/ultrasound



Comprehensive suite of transducers

The ACUSON P500 ultrasound system has a comprehensive suite of over 12 transducers supporting a diverse range of clinical applications.

Contents

Curved	3
Linear	4
Vector	5
Phased	8
Endocavity	10
Non-Imaging	11
Specialty	12

Curved



CH5-2 transducer

Part Number	1105184
Frequency Bandwidth	1.4–5.0 MHz
Selectable 2D Frequencies	2.5, 3.6, 5.0 MHz
Selectable THI (TEI) Frequencies	3.1, 3.6, 4.4, 5.0 MHz
Selectable Color Doppler Frequencies	2.0, 2.7, 3.3 MHz
Selectable Pulsed Wave Frequencies	2.0, 2.7, 3.3 MHz
Number of Elements	128
Footprint	61.1 mm
Maximum Field of View	57°
Maximum Display Depth	300 mm
Biopsy Guide Kit	Needle Guide Kit, PN 11253619
Biopsy Guide Angles	45° (A), 30.5° (B)
Exam Types	Abdominal, Obstetrics, Gynecology, Pelvis, Renal, Emergency Medicine, Vascular, Pediatrics
Design Attributes	<ul style="list-style-type: none"> • Wide bandwidth curved array transducer • Hanafy lens transducer technology • User-selectable MultiHertz multiple frequency imaging • Ergonomically designed form factor • Lightweight transducer with flexible cable

Linear



L10-5v transducer

Part Number	11319512
Frequency Bandwidth	3.5–13.0 MHz
Selectable 2D Frequencies	6.2, 8.0, 10.0 MHz
Selectable THI (TEI) Frequencies	7.3, 8.0, 9.4 MHz
Selectable Color Doppler Frequencies	4.0, 5.3, 6.2 MHz
Selectable Pulsed Wave Frequencies	4.0, 5.3, 6.2 MHz
Number of Elements	128
Footprint	38.4 mm
Maximum Field of View	N/A
Maximum Display Depth	10 cm
Biopsy Guide Kit	Needle Guide Set PN 11319513
Biopsy Guide Angles	51.5°, 38°
Exam Types	Breast, Cerebrovascular, Emergency Medicine, MSK, Small Part, Peripheral Arterial and Vein, Peripheral Venous, Pediatrics
Design Attributes	<ul style="list-style-type: none"> • Wide bandwidth linear transducer • Virtual format imaging • Hanafy lens transducer technology

Vector



VF10-5 transducer

Part Number	10146142
Frequency Bandwidth	4.0–11.4 MHz
Selectable 2D Frequencies	6.2, 8.0, 10.0 MHz
Selectable THI (TEI) Frequencies	7.3, 8.0, 9.4 MHz
Selectable Color Doppler Frequencies	4.0, 5.3, 6.2 MHz
Selectable Pulsed Wave Frequencies	4.0, 5.3, 6.2 MHz
Number of Elements	128
Footprint	38.4 mm
Maximum Field of View	N/A
Maximum Display Depth	100 mm
Biopsy Guide Kit	SG-3 Needle Guide Set, PN 11253617
Biopsy Guide Angles	52° (A), 40° (B)
Exam Types	Breast, Cerebrovascular, Emergency Medicine, MSK, Small Parts, Peripheral Arterial and Vein, Peripheral Venous, Pediatrics
Design Attributes	<ul style="list-style-type: none"> • Wide bandwidth linear transducer • Virtual format imaging • User-selectable MultiHertz imaging • Ergonomically designed form factor • 2D beam steering • Lightweight transducer with flexible cable



VF13-5 transducer

Part Number	11015188
Frequency Bandwidth	4.1–12.1 MHz
Selectable 2D Frequencies	7.3, 8.9, 11.4 MHz
Selectable THI (TEI) Frequencies	8.0, 8.8, 10.7 MHz
Selectable Color Doppler Frequencies	4.7, 5.7, 7.3 MHz
Selectable Pulsed Wave Frequencies	4.7, 5.7, 7.3 MHz
Number of Elements	128
Footprint	38.4 mm
Maximum Field of View	N/A
Maximum Display Depth	60 mm
Biopsy Guide Kit	SG-4 Needle Guide Set, PN 11253618
Biopsy Guide Angles	53°
Exam Types	Breast, Cerebrovascular, Emergency Medicine, MSK, Small Parts, Peripheral Arterial and Vein, Peripheral Venous, Pediatrics
Design Attributes	<ul style="list-style-type: none"> • Wide bandwidth linear transducer • Virtual format imaging • User-selectable MultiHertz imaging • Ergonomically designed form factor • 2D beam steering • Lightweight transducer with flexible cable



VF16-5 transducer

Part Number	11319509
Frequency Bandwidth	5.0–15.0 MHz
Selectable 2D Frequencies	8.0, 12.0, 15.0 MHz
Selectable THI (TEI) Frequencies	9.0, 10.3, 12.6, 14.0 MHz
Selectable Color Doppler Frequencies	5.3, 6.2 MHz
Selectable Pulsed Wave Frequencies	5.3, 6.2 MHz
Number of Elements	192
Footprint	34.8 mm
Maximum Field of View	N/A
Maximum Display Depth	6.0 cm
Biopsy Guide Kit	Needle Guide Set, PN 11319510
Biopsy Guide Angles	Free Angle
Exam Types	Breast, Cerebrovascular, Emergency Medicine, MSK, Sup MSK, Peripheral Arterial and Vein, Pediatrics
Design Attributes	<ul style="list-style-type: none"> • Wide bandwidth linear transducer • Virtual format imaging • Hanafy lens transducer technology

Phased



P4-2 transducer

Part Number	11015185
Frequency Bandwidth	1.3–4.4 MHz
Selectable 2D Frequencies	2.5, 3.1, 3.6 MHz
Selectable THI (TEI) Frequencies	3.0, 3.6, 4.0 MHz
Selectable Color Doppler Frequencies	2.2, 2.5, 3.3 MHz
Selectable Pulsed Wave Frequencies	2.2, 2.5, 3.3 MHz
Selectable Continuous Wave Frequencies	2.0 MHz
Number of Elements	64
Footprint	16.6 mm
Maximum Field of View	90°
Maximum Display Depth	30 cm
Biopsy Guide Kit	N/A
Biopsy Guide Angles	N/A
Exam Types	Abdominal, Obstetrics, Emergency Medicine, Cardiac
Design Attributes	<ul style="list-style-type: none"> • Wide bandwidth phased array transducer • User-selectable MultiHertz imaging • Ergonomically designed form factor • Lightweight transducer with flexible cable



P8-4 transducer

Part Number	11319508
Frequency Bandwidth	2.7–8.0 MHz
Selectable 2D Frequencies	4.2, 5.7, 6.7 MHz
Selectable THI (TEI) Frequencies	5.4, 6.2, 7.2 MHz
Selectable Color Doppler Frequencies	3.6, 4.4 MHz
Selectable Pulsed Wave Frequencies	3.6, 4.4 MHz
Number of Elements	64
Footprint	9.6 mm
Maximum Field of View	89°
Maximum Display Depth	14.0 cm
Biopsy Guide Kit	Not available
Biopsy Guide Angles	N/A
Exam Types	Neonatal Head, Pediatric Abdomen, Pediatric Echo
Design Attributes	<ul style="list-style-type: none"> • Wide bandwidth phased array transducer • User-selectable MultiHertz imaging • Ergonomically designed form factor • Lightweight transducer with flexible cable

Endocavity



EC9-4 transducer

Part Number	10785548
Frequency Bandwidth	3.3–10.3 MHz
Selectable 2D Frequencies	5.0, 6.7, 8.0 MHz
Selectable THI (TEI) Frequencies	5.7, 6.6, 9.4 MHz
Selectable Color Doppler Frequencies	4.0, 5.3, 6.2 MHz
Selectable Pulsed Wave Frequencies	4.0, 5.3, 6.2 MHz
Number of Elements	128
Footprint	26.2 mm
Maximum Field of View	131°
Maximum Display Depth	140 mm
Biopsy Guide Kit	Disposable PN 11235348 Reusable PN 11253622
Biopsy Guide Angles	2°
Exam Types	Obstetrics, Gynecology, Emergency Medicine, Prostate
Design Attributes	<ul style="list-style-type: none"> • User-selectable MultiHertz imaging • Ergonomically designed form factor • Lightweight transducer with flexible cable

Non-Imaging



CW2 transducer

Part Number	11335984
Frequency Bandwidth	N/A
Selectable 2D Frequencies	N/A
Selectable THI (TEI) Frequencies	N/A
Selectable Color Doppler Frequencies	N/A
Selectable Pulsed Wave Frequencies	N/A
Number of Elements	2
Footprint	10.8 mm
Maximum Field of View	N/A
Maximum Display Depth	N/A
Biopsy Guide Kit	Not available
Biopsy Guide Angles	N/A
Exam Types	Cardiac, Pediatric Echo, Adult Echo



CW5 transducer

Part Number	11335985
Frequency Bandwidth	N/A
Selectable 2D Frequencies	N/A
Selectable THI (TEI) Frequencies	N/A
Selectable Color Doppler Frequencies	N/A
Selectable Pulsed Wave Frequencies	N/A
Number of Elements	2
Footprint	8.9 mm
Maximum Field of View	N/A
Maximum Display Depth	N/A
Biopsy Guide Kit	Not available
Biopsy Guide Angles	N/A
Exam Types	Cerebrovascular, Pediatric Echo

Specialty



Clinical applications for ACUSON AcuNav 8F ultrasound catheter:
 adult intracardiac echocardiography

ACUSON AcuNav 8F ultrasound catheter

Part Number	8267996
Frequency Bandwidth	3.0–10.0 MHz
Selectable 2D Frequencies	5.0, 6.7, 8.9 MHz
Selectable THI (TEI) Frequencies	N/A
Selectable Color Doppler Frequencies	4.0, 5.0 MHz
Selectable Pulsed Wave Frequencies	4.0, 5.0 MHz
Number of Elements	64
Footprint	7.0 mm
Maximum Field of View	90°
Maximum Display Depth	160 mm
Biopsy Guide Kit	Not available
Biopsy Guide Angles	N/A
Exam Types	Intracardiac
Design Attributes	<ul style="list-style-type: none"> • 8 french catheter (2.7 mm diameter) • 90 cm insertable length • Sterile, single-use advanced miniaturization ACUSON AcuNav ultrasound catheter family • Reusable SwiftLink catheter connector • Four-way steering in two planes: 160° in each direction • Longitudinal side-fire imaging • Vector imaging format



**Clinical applications
for ACUSON AcuNav 10F
ultrasound catheter:**
adult intracardiac
echocardiography

ACUSON AcuNav 10F ultrasound catheter

Part Number	8255790
Frequency Bandwidth	2.2–11.0 MHz
Selectable 2D Frequencies	5.0, 6.7, 8.9 MHz
Selectable THI (TEI) Frequencies	N/A
Selectable Color Doppler Frequencies	4.0, 5.0 MHz
Selectable Pulsed Wave Frequencies	4.0, 5.0 MHz
Number of Elements	64
Footprint	7.0 mm
Maximum Field of View	90°
Maximum Display Depth	160 mm
Biopsy Guide Kit	Not available
Biopsy Guide Angles	N/A
Exam Types	Intracardiac
Design Attributes	<ul style="list-style-type: none"> • 10 french catheter (3.3 mm diameter) • 90 cm insertable length • Sterile, single-use advanced miniaturization ACUSON AcuNav ultrasound catheter family • Reusable SwiftLink catheter connector • Four-way steering in two planes: 160° in each direction • Longitudinal side-fire imaging • Vector imaging format

The products/features mentioned in this document may not be commercially available in all countries. Due to regulatory reasons, their future availability cannot be guaranteed. Please contact your local Siemens Healthineers organization for further details.

ACUSON, ACUSON AcuNav, ACUSON P500, MultiHertz and SwiftLink are trademarks of Siemens Medical Solutions USA, Inc.

Siemens Healthineers Headquarters

Siemens Healthcare GmbH
Henkestr. 127
91052 Erlangen, Germany
Phone +49 9131 84-0
siemens-healthineers.com

Legal Manufacturer

Siemens Medical Solutions USA, Inc.
Ultrasound
22010 S.E. 51st Street
Issaquah, WA 98029, USA
Phone: 1-888-826-9702
siemens-healthineers.com/ultrasound