



ROTOR SPECIFICATIONS

Type	Fixed Angle	
Material	Aluminum	
Capacity	12 x 50 mL	
Maximum Speed	17,000 rpm	
Tube Dimensions Ø x L	29 x 108 mm	
Angle	34°	
K Factor	747	
Net Weight	10.1 kg/22.3 lbs	
Warranty	10 years	
Certifications¹		
	RCF	RADIUS
Maximum	41,837 xg	129.6 mm
Minimum	17,819 xg	55.2 mm

ROTOR AND ACCESSORIES ORDERING INFORMATION

		THERMO SCIENTIFIC		
		SORVALL RC-6 Plus Series	SORVALL Evolution RC Series	SORVALL RC-5 Plus Series
SA-600	Max. Speed	16,500 rpm	17,000 rpm	16,500 rpm
	Max. RCF	39,412 xg	41,837 xg	39,412 xg

SA-600 Rotor Package includes:

Description	Cat. No.
SA-600 Rotor	28500
Rotor Cover Assembly	12291
Cover O-ring	60810
Rotor Extractor	01031
Instruction Manual	28505

Accessories:

Description	Cat. No.
Ultracrimp Sealing Tool and Crimp Gauge	03920
Crimp Gauge Replacement	03919
Extra Plugs and Caps	03999
Rotor Cap	03538

¹ Biocontainment certification by the Public Health Laboratory Service, Centre for Applied Microbiological Research, Porton Down, UK, shown to be suitable for use with materials up to ACDP Category 3 as categorized by the Advisory Committee on Dangerous Pathogens.

LABWARE ORDERING INFORMATION

Tube Vol. (mL)	Vol. Fill (mL)	Description	Cat. No.	Qty. /Pkg.	Tubes /Rotor	Max. Speed (rpm)	Max. RCF (xg)	Dims ØxL (mm)	REQUIRED TUBE CLOSURES, ADAPTERS, TOOLS & ACCESSORIES			
									Type	Cat. No.	Qty. /Pkg.	Description
50.0	50.0	PA Ultracrimp Tube	03528	25	12	17,000	41,837	29 x 108	Closure	Included	25	Plugs and Aluminum Caps
									Accessory	03538	1	Rotor Cap
									Accessory	03529	1	Tube Racks
									Accessory	03920	1	Crimp Sealing Tool
50.0	37.0	PP Flanged Tube	03147	25	12	17,000	41,837	29 x 102	Closure	03268	1	PP Snap-on
50.0	36.0	PC Flanged Tube	03146	25	12	17,000	41,837	29 x 102	Closure	03268	1	PP Snap-on
50.0	46.0	PA Thin-Walled Tube	03139	25	12	17,000	41,837	28 x 104	—	—	—	—
50.0	46.0	FEP Oak Ridge Tube	3114-0050	10	12	17,000	41,837	29 x 108	Closure	Included	10	FEP Sealing
50.0	42.0	Nalgene™ PPCO Oak Ridge Tube	3139-0050	50	12	17,000	41,837	29 x 107	Closure	Included	50	PP Sealing
50.0	43.0	Nalgene PC Oak Ridge Tube	3138-0050	50	12	17,000	41,837	29 x 108	Closure	Included	50	PP Sealing
50.0	50.0	SS Flanged Tube	00517	1	12	17,000	41,837	28 x 101	Closure	00518	1	SS Sealing
									Tool	01014	1	Wrench
30.0	28.0	PC Oak Ridge Tube	314348	25	12	17,000	41,837	25 x 94	Closure	314347	1	Aluminum Sealing Assembly
									Adapter	00419	1	1 place/adapter
									Tool	314353	1	Tube Extractor Tool
30.0	28.0	PP Oak Ridge Tube	314349	25	12	17,000	41,837	25 x 94	Closure	314347	1	Aluminum Sealing Assembly
									Adapter	75003027	1	1 place/adapter
									Tool	314353	1	Tube Extractor Tool
16.0	13.0	PP Flanged Tube	03244	50	12	17,000	41,837	18 x 100	Closure	03299	50	PP Snap-On
									Adapter	75003026	1	1 place/adapter
16.0	14.0	PC Flanged Tube	03243	50	12	17,000	41,837	18 x 100	Closure	03269	1	PP Snap-On
									Adapter	75003026	1	1 place/adapter
12.0	12.0	GL Pyrex™ Tube	03109	50	12	5,000	3,619	18 x 102	Adapter	00363	1	1 place/adapter
12.0	10.0	PP Flanged Tube	03116	50	12	17,000	41,837	16 x 100	Closure	03266	50	PP Nonsealing
									Adapter	00402	1	1 place/adapter
12.0	11.0	PC Flanged Tube	03115	50	12	17,000	41,837	16 x 100	Closure	03266	50	PP Nonsealing
									Adapter	00402	1	1 place/adapter
10.0	9.1	PP Oak Ridge Tube	03929	50	12	17,000	41,837	16 x 83	Closure	03279	25	PP Sealing
									Adapter	75003024	1	1 place/adapter
10.0	9.1	PC Oak Ridge Tube	03020	25	12	17,000	41,837	16 x 83	Closure	03279	25	PP Sealing
									Adapter	75003024	1	1 place/adapter
7.0	6.0	PC Flanged Tube	03120	50	12	17,000	41,837	13 x 100	Closure	03265	50	PP Snap-On
									Adapter	00473	1	1 place/adapter
7.0	6.0	PP Flanged Tube	03121	50	12	17,000	41,837	13 x 100	Closure	03265	50	PP Snap-On
									Adapter	00473	1	1 place/adapter
4.0	3.0	PP Flanged Tube	03105	50	12	17,000	41,837	11 x 75	Closure	03264	50	PP Snap-On
									Adapter	75003023	1	1 place/adapter
4.0	3.0	PC Flanged Tube	03104	50	12	17,000	41,837	11 x 75	Closure	03264	50	PP Snap-On
									Adapter	75003023	1	2 places/adapter
3.0	3.0	GL Pyrex Tube	03100	50	24	5,000	3,619	10 x 75	Adapter	00364	1	2 places/adapter
1.5	1.5	Conical Microtube	—	—	24	17,000	41,837	11 x 42	Adapter	75003029	1	2 places/adapter
1.5	1.5	Conical Microtube	314352H01	100	24	17,000	41,837	11 x 41	Adapter	75003029	1	2 places/adapter

© 2014 Thermo Fisher Scientific Inc. All rights reserved. Pyrex is a registered trademark of Corning Inc. All other trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

For more information, please visit
www.thermoscientific.com/rotors.

DSCFGSSA600 1114

Thermo
 S C I E N T I F I C

Part of Thermo Fisher Scientific