

10 μ L, Gastight Syringe, Cemented Needle (N), PN: 80000

Specification Sheet (Part/REF # 80000)



The 1700 series syringes are the gas tight version of the original 700 series syringes. This series of gas tight syringes is ideal for dispensing volumes from 1 μ L up to 500 μ L. A variety of different terminations and needle options are available in this series.

Product Specifications

Volume	10 μ L
Syringe Type	Gastight
Syringe Series	1700
Termination	Cemented Needle (N)
Needle	Cemented Needle
Gauge	26s gauge
Point Style	2: Curved, Beveled
Needle Length	2 inch (51 mm)
Fluid Path	SST, Borosilicate glass, PTFE
Autoclavable	No
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.018 inches (0.460 mm)
Barrel Outer Diameter	0.260 inches (6.60 mm)
Needle Inner Diameter	0.005 inches (0.13 mm)
Needle Outer Diameter	0.0187 inches (0.47 mm)
Std Needle Dead Volume	0.64 μ L
Sales Quantity	1 syringe per pack

Specifications are subject to change without notice

<https://www.hamiltoncompany.com/laboratory-products/syringes/80000>

Spec. Version B